

JET 550

Frontlit

•APPLICATIONS

- One side printing
 - Digital printing: solvent / eco-solvent and UV inks
 - Screenprinting: solvent and UV inks
 - Indoor / Outdoor
- Billboards / banners / POS / signage / wall covering

•PRODUCT INFORMATION

Super wide format: 2.50 / 3.15 / 3.20 m
Rolls of: 60 and 250 lm / printable side inside

Wide format: 0.76 / 1.04 / 1.37 / 1.56 / 2.50 m
Rolls of: 30 lm / printable side outside

Screenprinting: 0.90 / 1.00 / 1.10 m
Packaging: 4 rolls of 60 lm / pallet – printable side inside
2.50 / 3.15 / 3.20 m

Rolls of 60 and 250 lm / printable side inside

For special requirements:
Other widths available: 2.24 m / 2.78 m - please contact us

- Weight 575 g/m²
- Base cloth high tenacity polyester 1100 Dtex
- Coating PVC coating, system LOWICK
- Finish satin inkjet lacquer one side
- Colour white 7325

•PRODUCT CHARACTERISTICS

- | | | |
|-------------------------|-----------------|----------------|
| - Tensile strength | 200/210 daN | NF EN ISO 1421 |
| - Tear strength | 30/20 daN | DIN 53363 |
| - Adhesion | 7 daN/5 cm | NF EN ISO2411 |
| - Translucency | 6 % | XPT 54 199 |
| - Thickness | 0.47 mm | |
| - Temperature stability | | |
| in Celsius | - 30°C to +70°C | |
| in Fahrenheit | - 22°F to +158° | |
| - F/R | < 100 mm/mn | DIN 75200 |

Average values +/- 10% non contractual

03/2007